

Model CS5-36 COOL-SPACE™ Portable Evaporative Cooler



SPECIFICATION SHEET **CS5-36-VD**

Housing - Constructed of roto-molded corrosion free polyethylene mounted on 4" casters.

Cooling Media - 8" thick high efficiency cross-corrugated angle fluted specially formulated cellulose material treated with a thermosetting resin with edge guard.

Fan - 36 inch industrial duty aluminium or plastic, 4-blade construction for quieter operation.

Fan Motor - High efficiency, totally enclosed 1/2 h.p.

Single Speed Direct Drive:

9,500 CFM @ .15" S.P.

115 / *230 volt / 1 ph / 60 hz / 6.4 amps

Variable Speed Direct Drive:

100 to 9,500 CFM @ .15"S.P.

115 / *230 volt / 1 ph / 60 hz / 6.3 amps

Circulation Pump - Submersible maintenance free

115 / *230 volt / 1 ph / 60 hz / 1.5 amps

Water Supply - Garden hose connection suitable for pressured, up to 60 lbs., or gravity feed. Water level regulated by a float valve.

Water Reservoir - Internal 46 gallon capacity.

Cooling Coverage Area - Approx. 2,500 sq. ft.

Dimensions - 62" Wide x 31 1/2" Deep x 69" Height

Shipping Weight - 325 lbs.

*230 Volt Models available consult factory for pricing



CS5-36-VD

 **COOL-SPACE™**
PORTABLE EVAPORATIVE COOLERS

Advanced Radiant Systems, Inc.
315 N. Madison St - Fortville, IN 46040
12910 Tel. (317) 577-0417 - Fax. (317) 485-0118
TF. (800) 557-5716 - www.cool-space.com